

CLAIMS

What is claimed is:

- 5 1. A disabling method and system of a stolen car is comprised of 1)
disabling the car engine by disconnecting the electric power
supply to the ignition plug according to the order of the main
computer, 2) puncturing rear tires with two sets of bullets, which
is connected to an electric trigger line connected to the main
10 computer in a short barrel installed at the inside of one rear wheel
cover and another two sets of bullets in a short barrel installed at
the inside of the opposite rear wheel cover, and 3) activating the
anti-theft alarm which is connected to the main computer by
dialing the number of a pager which is installed behind the driving
15 gauge board and a secret code with conventional telephone.
2. A disabling method and system of a stolen car comprised of 1)
disabling the car engine by disconnecting the electric power supply
to the ignition plug according to the order of the main computer, 2)
20 puncturing rear tires with hook blade which is connected to a
spring and one end of the hook blade is pivotally affixed to the rear
wheel cover with bolt and nut, installed at the inside of rear wheel
cover and another set of hook blade also connected to a spring is
installed at the inside of another rear wheel cover of opposite site
25 and the other side of the hook blade is captured by a trigger which
is connected to an electric trigger line which is connected to the

main computer (6) of FIG. 4. , and 3) activating the anti-theft alarm which is connected to the main computer by dialing the number of a pager, which is installed behind the driving gauge board, and a secret code with conventional telephone.